### **ROUGH TERRAIN ELECTRIC**



### AHS 10 RTE AHS 12 RTE COMPACT

# Oustanding performance, both inside and outside

- Suitable for all terrains allowing the operator to work without noise and fumes
- Tight turning radius allowing an excellent manoeuvrability in confined areas
- Foam filled and nonmarking tires with rough terrain profile
- **G**round clearance of 25 cm
- Load capacity up to 565 kg (10 RTE)
- > Driveable at full height
- Long working cycles

### Robust, reliable, easy to maintain





## **ROUGH TERRAIN ELECTRIC**

TECHNICAL DATA	AHS 10 RTE	AHS 12 RTE
Working height	10.28 m	12.06 m
Platform height	8.28 m	10.06 m
Gradeability	25 %	25 %
Lift capacity	565 kg	450 kg
Platform length - outside	2.45 m	2.45 m
Platform length - extended	3.7 m	3.7 m
Length - extension	1.2 m	1.2 m
<b>G</b> Platform width - outside	1.45 m	1.45 m
Storage height	1.59 m	1.71 m
C Height - stowed	2.44 m	2.56 m
B Overall width	1.78 m	1.78 m
A Length	2.64 m	2.64 m
D Wheelbase	1.84 m	1.84 m
Ground clearance	25 cm	25 cm
Ground clearance - Pothole guards deployed	N/A	N/A
Drive speed	0,8 - 5,8 km/h	0.8 - 5.8 km/h
Driveable at full height up to	8.28 m	10.06 m
Tilt	3 °	3 °
Lift / lower speed	35 s / 35 s	43 s / 43 s
Turning radius - outside	3.73 m	3.73 m
Non-marking tires	26x12-12	26x12-12
Batteries	48 V - 255 Amph (C5)	48 V - 255 Amph (C5)
Hydraulic system capacity	63 I	63 l
Weight	3 305 kg	3 675 kg



Working At Height Limited (Southern Office) Amberley Court Old Elstead Road Milford Surrey GU8 5EB

Tel: 01483 415 410 Fax: 01483 417 719

#### Working At Height Limited

(Northern Office) The Portergate Ecclesall Road Sheffield South Yorkshire S11 8NX

Tel: 0114 209 6206 Fax: 0114 209 6001

#### Suppliers of:

Powered Access Platforms Aerial Work Platforms Runabout Access Platforms Scissor Lifts Articulating Boom Access Platforms Telescopic Boom Access Platforms Material Lifts Telehandlers MEWPS Training

### 

### **STANDARD EQUIPMENT**

- Extended platform
- Proportional lift and drive
- Removable control box in platform

-4 -3

- Battery charge indicator
- Battery charger with automatic stop
- Lanyard attachment points
- 2 wheel-drive
- Free wheeling device
- Tilt controller
- Load Management System in the platform
- Manual platform lowering valve

**OPTIONS AND ACCESSORIES** 

- Hydraulic brakes
- Towing hooks
- Horn
- Hourmeter

Flashing lightTravel alarm

- Power to platformBiodegradable hydraulic oil
- Outriggers (Increase machine weight by 240 kg)

\_

2

1

AHS 12 RTE