

## CUSTOMIZED VERSATILITY

With three base models and many accessories to choose from, the Genie® Lift™ is ideal for all your material handling needs. From the GL™-4 that lifts up to 500 lbs (227 kg) to 5 ft 11 in (1.80 m) to the GL™-12 that lifts up to 350 lbs (159 kg) to heights up to 13 ft 9.5 in (4.2 m), the Genie® Lift™ is perfect for a variety of jobs. The Genie® Lift™ is well suited for shipping/receiving, lifting heavy material to or from shelves, installing and repairing HVAC components, lifting and moving automotive parts, and other manufacturing applications. Compact and versatile, this unit is also easily loaded in a pickup truck for convenient transport.



### STRADDLE BASE

Adjustable base legs straddle loads or fixed objects up to 36 in (91 cm) wide. Perfect for lifting small pallets, appliances and other bulky objects. (GL™-4, GL™-8, GL™-10, GL™-12)

### COUNTERWEIGHT BASE

Short leg length lets you get close to your load. Excellent for accessing loads on countertops or shelves above fixed objects. Designed for use on level surfaces. (GL™-4, GL™-8, GL™-10)

### STANDARD BASE

Compact design allows you to lift and maneuver in congested work areas. Great for general lifting and material delivery. Low loading height. (GL™-4, GL™-8)

**Choose from three bases to customize the Genie® Lift™ for your job — it can be used as a hand truck, forklift or dolly for maximum versatility and value.**



### PLATFORM FOR LOAD HANDLING

The optional load platform fits easily over forks to handle odd-shaped loads and can also be used as a portable work table.



### WHEELS AND CASTERS

8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual-wheel, front-swivel casters are standard on the standard and straddle base models. 5 in (12 cm) rear-swivel casters with side brakes and fixed 4 in (10 cm) front wheels are standard on the counterweight base model. Optional pneumatic rear tires and foot-release brake available (standard and straddle base only).



### BOOM FOR ADDED VERSATILITY

The boom option turns your Genie® Lift™ into a vertical crane or hoist capable of lifting 210 to 500 lbs (95 to 227 kg) with up to 20 in (51 cm) of reach.



### LADDER FOR INCREASED ACCESS

Attaching the sturdy aluminum ladder accessory makes your Genie® Lift™ a combination lift truck and stepladder for increased access to lifting and installation tasks. (Available on standard and straddle base models; not available with electric winch option.) The standard winch can be used while the ladder is in use or stowed.

### COMPACT, MANEUVERABLE DESIGN

The telescoping aluminum frame design makes the unit extremely compact. Plus, the durable steel forks can be reversed for greater flexibility. In addition, the winch handle is reversible, and a hold-down mechanism secures the carriage for easy transport and storage.


### ELECTRIC WINCH FOR FASTER LIFTING

The electric winch option comes with a battery pack and an automatic charger that shuts itself off when fully charged. The electric winch control cable extends 5.8 ft (1.77 m) for added mobility. It's available with the straddle base and counterweight base models. A caster option kit is required for use with straddle base model (factory-installed only).

### GENIE® LIFT™ MODELS AVAILABLE

GL™-4 | GL™-8 | GL™-10 | GL™-12

# Specifications



MODELS	GL™-4		GL™-8		GL™-10		GL™-12	
MEASUREMENTS	US	Metric	US	Metric	US	Metric	US	Metric
<b>A</b> Height - stowed <sup>1, 2, 3</sup>	5 ft 7.5 in	1.72 m	5 ft 7.5 in	1.72 m	6 ft 6.5 in	2.00 m	7 ft 7 in	2.31 m
maximum forks down	4 ft 1.5 in	1.26 m	8 ft 3 in	2.51 m	9 ft 10.5 in	3.01 m	12 ft	3.66 m
maximum forks up	5 ft 11 in	1.80 m	10 ft .5 in	3.06 m	11 ft 8 in	3.56 m	13 ft 9.5 in	4.20 m
minimum forks down	3.5 in	.09 m	3.5 in	.09 m	2 in	.05 m	2 in	.05 m
<b>STANDARD BASE</b>								
<b>B</b> Length - stowed	1 ft	.30 m	1 ft	.30 m	—	—	—	—
operating	2 ft 10.75 in	.88 m	2 ft 10.75 in	.88 m	—	—	—	—
<b>C</b> Width: outside	2 ft .75 in	.63 m	2 ft .75 in	.63 m	—	—	—	—
Weight - standard caster options	113 lbs	51 kg	132 lbs	60 kg	—	—	—	—
pneumatic caster options	117 lbs	53 kg	136 lbs	62 kg	—	—	—	—
<b>STRADDLE BASE</b>								
Length - stowed	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m
operating	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m
Width - stowed <sup>4</sup>	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m
maximum <sup>4</sup>	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m
maximum inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m
Weight - standard caster options	126 lbs	57 kg	145 lbs	66 kg	149 lbs	68 kg	154 lbs	70 kg
pneumatic caster options	130 lbs	59 kg	149 lbs	68 kg	153 lbs	69 kg	158 lbs	72 kg
4-point caster option	139 lbs	63 kg	158 lbs	72 kg	162 lbs	73 kg	167 lbs	76 kg
<b>COUNTERWEIGHT BASE</b>								
Length - operating	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	—	—
Width - stowed <sup>4</sup>	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	—	—
maximum <sup>4</sup>	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	—	—
maximum inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	—	—
Weight - standard caster options	392 lbs	178 kg	411 lbs	186 kg	433 lbs	196 kg	—	—

PRODUCTIVITY								
Load height minimum	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m
Ground clearance - center <sup>1, 2, 3</sup>	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m
Average cranks - standard winch	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m
electric winch	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec
Fork length	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m
Fork width	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m
Load platform length	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m
Load platform width	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
Load capacity at								
12 in (30 cm) load center	500 lbs	227 kg	400 lbs	181 kg	350 lbs	159 kg	350 lbs	159 kg
Boom length	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm
Boom attachment points	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm

POWER	
Power source	reversible standard winch or electric winch

<sup>1</sup> The 10 in pneumatic rear wheel option will add 1 in (2.5 cm) to these specifications. <sup>3</sup> The 4-point caster option B will add 1 in (2.5 cm) to these specifications.  
<sup>2</sup> The counterweight base will add 1 in (2.5 cm) to these specifications. <sup>4</sup> Outside dimensions.

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### FORK OPTIONS

- Standard forks
- Load platform
- Boom

#### POWER OPTIONS

- Standard winch
- Electric winch

#### BASE OPTIONS

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

#### WHEEL/CASTER OPTIONS

##### Straddle and standard base

- 8 in (20 cm) non-marking rear wheels
- Pneumatic rear tire option
- 2 in (5 cm) dual wheel front swivel casters

##### Counterweight base

- 5 in (12 cm) rear swivel casters with side brakes
- 4 in (10 cm) fixed front wheels

##### Straddle base

- 4 point caster option

### STANDARD FEATURES

#### MEASUREMENTS

##### GL™-4

- 5 ft 11 in (1.80 m) maximum lift height
- Up to 500 lb (227 kg) load capacity

##### GL™-8

- 10 ft .5 in (3.06 m) maximum lift height
- Up to 400 lb (181 kg) load capacity

##### GL™-10

- 11 ft 8 in (3.56 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

##### GL™-12

- 13 ft 9.5 in (4.20 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

#### PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminum construction
- Single door access
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

#### POWER

- Standard winch
- Reversible winch handle for easy storage



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Load platform
- Boom
- Aluminum ladder (standard and straddle base only)
- Pneumatic rear tires (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options

#### POWER

- Electric winch (straddle and counterweight base only)
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases
- Electric winch option comes standard with battery and automatic charger that shuts off when fully charged.

#### Working At Height Limited

(Southern Office)  
Amberley Court  
Old Elstead Road  
Milford  
Surrey  
GU8 5EB

Tel: 01483 415 410  
Fax: 01483 417 719

#### Working At Height Limited

(Northern Office)  
The Portergate  
Ecclesall Road  
Sheffield  
South Yorkshire  
S11 8NX

Tel: 0114 209 6206  
Fax: 0114 209 6001

#### Suppliers of:

Powered Access Platforms  
Aerial Work Platforms  
Runabout Access Platforms  
Scissor Lifts  
Articulating Boom Access Platforms  
Telescopic Boom Access Platforms  
Material Lifts  
Telehandlers  
MEWPS Training