

## Industrial Tower System

Tested and certified to BSEN1004:2004  
 Dual brake on/off system  
 Quick release pull rings and stainless steel pin on all bracings  
 Smooth & ribbed tubing on braces for quick identification  
 Wide ladder and hexagonal rung for easier climb & additional safety  
 Large articulating rubber feet on all stabilisers  
 3T compatible

## Technical Specification

Two widths available 1.45m & 0.85m  
 Three lengths available 1.8m, 2.5m & 3.2m  
 Extruded tube diameter 50.8mm  
 Extruded tube thickness 1.6mm  
 3mm frame spigots  
 Extruded aluminium ladder stile & rung  
 Heat treated gravity castings  
 Stainless steel bracing lock pins  
 Articulating rubber feet  
 Spring steel frame lock clips  
 Reinforced platforms



## Single Width Mobile Tower Schedule

Single Width - Platform Heights	internal or external work															internal work only							
	1.2	1.7	2.2	2.7	3.2	3.7	4.2	4.7	5.2	5.7	6.2	6.7	7.2	7.7	8.2	8.7	9.2	9.7	10.2	10.7	11.2	11.7	12.2
150mm dual locking castor	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Adjustable Leg	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
2 rung span frame	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1
2 rung ladder frame	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1
3 rung span frame	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-
3 rung ladder frame	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-
4 rung span frame	1	-	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6
4 rung ladder frame	1	-	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6
1.8m - 2.5m hatch deck	1	1	1	1	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6	6
1.8m - 2.5m horizontal brace	6	6	6	6	10	10	10	14	14	14	14	18	18	18	18	22	22	22	26	26	26	26	26
2.1m - 2.7m diagonal brace	2	3	3	5	5	7	7	9	9	11	11	13	13	15	15	17	17	19	19	21	21	23	23
1.8m - 2.5m side toeboard	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Single width toeboard end	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Standard stabiliser	-	-	4	4	4	4	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Telescopic stabiliser	-	-	-	-	-	-	-	4	4	4	4	-	-	-	-	4	4	4	-	-	-	-	-
Large telescopic stabiliser	-	-	-	-	-	-	-	-	-	-	-	4	4	4	4	-	-	-	4	4	4	4	4

Component Schedule based on 3T specification.

## Double Width Mobile Tower Schedule

Single Width - Platform Heights	internal or external work															internal work only							
	1.2	1.7	2.2	2.7	3.2	3.7	4.2	4.7	5.2	5.7	6.2	6.7	7.2	7.7	8.2	8.7	9.2	9.7	10.2	10.7	11.2	11.7	12.2
150mm dual locking castor	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Adjustable Leg	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
2 rung span frame	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1
2 rung ladder frame	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1	-	-	1	1
3 rung span frame	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-
3 rung ladder frame	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-	1	-
4 rung span frame	1	-	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6
4 rung ladder frame	1	-	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6
1.8m - 2.5m hatch deck	1	1	1	1	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6	6
1.8 - 2.5 standard deck	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1.8m - 2.5m horizontal brace	6	6	6	6	10	10	10	14	14	14	14	18	18	18	18	22	22	22	22	26	26	26	26
2.1m - 2.7m diagonal brace	2	3	3	5	5	7	7	9	9	11	11	13	13	15	15	17	17	19	19	21	21	23	23
1.8m - 2.5m side toeboard	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Double width toeboard end	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Standard stabiliser	-	-	4	4	4	4	4	4	4	4	4	-	-	-	-	-	-	-	-	-	-	-	-
Telescopic stabiliser	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-	4	4	4	-	-	-	-	-
Large telescopic stabiliser	-	-	-	-	-	-	-	-	-	-	-	-	4	4	4	-	-	-	4	4	4	4	4

Component Schedule based on 3T specification.